

TopMountTrack




TopMountTrack

The **TopMountTrack** is a smooth running low profile track system. Its versatility makes it popular for a range of opening types including pocket, barn, partition and multi-sliding applications. The clip on fascia is suitable for use in barn door and partition applications.


CS TopMountTrack is ideal where longevity of use and smooth operation are required.

Product Specifications


Single Track




Double Track - 1-3/8"




Double Track - 1-3/4"



Triple Track - 1-3/8"



Triple Track - 1-3/4"



How to Specify

- Choose track configuration: single, double or triple
- Specify door thickness: 1-3/8" and 1-3/4" doors
- Specify track length
Available in 6, 8, 12, and 24' pre-cut lengths
- Determine Application
Multiple tracks can be used for bypass and collection (telescoping) applications
- Choose a carriage pack (one per door)
(Includes carriages, mounting plates, T-Guide, fixing screws, adjusting wrench and installation instructions)
 - M6 (200 lb)
 - M8 (500lb)
 - SofStop
 - SofStop HD
 - CS Door Collection System (For multiple tracks)
(includes M6 or M8 carriage pack plus door collection system for 2 door or 3 door setup)
- Fascia and End Caps (Optional): Specify finish

© All copyright and other property in this document is reserved by Cavity Sliders USA Inc. Details and specifications are subject to change without notice. Whilst all care is taken to ensure the accuracy of all information, no responsibility will be accepted for any errors or omissions. 12/2024

CavitySliders.com

sales@cavitysliders.com

(888) 466-0030

Features

- Suitable for incorporating into pocket frame assemblies for a smooth running high end system.
- Double and Triple Tracks can be used for bypass and collection systems.
- Pre-machined mounting holes.

Technical Information

Track	Single	Double	Triple
Track Finish	Mill-finish	Mill-finish	Mill-finish
Fascia Finish	Clear or Bronze Anodized	Clear or Bronze Anodized	Clear or Bronze Anodized
Door Thickness	1-3/8" or 1-3/4" (35 or 45mm)	1-3/8" or 1-3/4" (35 or 45mm)	1-3/8" or 1-3/4" (35 or 45mm)
Max Door Weight	500lb (240kg)	500lb (240kg)	500lb (240kg)
Max Door Weight (SofStop)	350lb (158kg)	350lb (158kg)	350lb (158kg)

SofStop® Features & Options

- High quality mechanism independently tested to 100,000 cycles
- Soft close mechanism is hidden from sight, yet remains fully serviceable










Standard	M6 (200lb/90kg)		
	M8 (500lb/240kg)		
CS SofStop	Minimum Door Width		
	No Stop	1 Stop	2 Stops
0 - 200 lb (90kg)	23" (584mm)	26" (660mm)	28" (711mm)
CS SofStop HD	Minimum Door Width		
	No Stop	1 Stop	2 Stops
0 - 350 lb (160kg)	26" (660mm)	29" (737mm)	31" (787mm)



TopMountTrack Product Codes

Tracks

Tracks are available in popular pre-cut lengths or can be cut to custom lengths between 6 and 24ft (to the nearest foot). A per foot rate applies to custom lengths, which includes cutting fee.

Item	Description	Length	Code
	CS TopMountTrack - Single	6ft	CT6
		8ft	CT8
		12ft	CT12
		24ft	CT24
		Custom	CTNSS
	CS TopMountTrack - Single Fascia Clear Anodized Suits 1-3/8" or 1-3/4" door	6ft	FNA-6
		8ft	FNA-8
		12ft	FNA-12
		24ft	FNA-24
		Custom	FNA-NSS
	CS TopMountTrack - Single Fascia Bronze Anodized Suits 1-3/8" or 1-3/4" door	6ft	FBA-6
		8ft	FBA-8
		12ft	FBA-12
		24ft	FBA-24
		Custom	FBA-NSS
	CS TopMountTrack - Single End Cap (x1) - Fascia One Side	Clear Anodized	ZK00427
	CS TopMountTrack - Single End Cap (x1) - Fascia One Side	Bronze Anodized	ZK00430
	CS TopMountTrack - Single End Cap (x1) - Fascia Both Sides	Clear Anodized	ZK00428
	CS TopMountTrack - Single End Cap (x1) - Fascia Both Sides	Bronze Anodized	ZK00429
	CS TopMountTrack - Double 1-3/8" door thickness	6ft	TSTM2-138-6
		8ft	TSTM2-138-8
		12ft	TSTM2-138-12
		24ft	TSTM2-138-24
		Custom	TSTM2-138-NSS
	CS TopMountTrack - Double 1-3/4" door thickness	6ft	TSTM2-134-6
		8ft	TSTM2-134-8
		12ft	TSTM2-134-12
		24ft	TSTM2-134-24
		Custom	TSTM2-134-NSS
	CS TopMountTrack - Triple 1-3/8" door thickness	6ft	TSTM3-138-6
		8ft	TSTM3-138-8
		12ft	TSTM3-138-12
		24ft	TSTM3-138-24
		Custom	TSTM3-138-NSS
	CS TopMountTrack - Triple 1-3/4" door thickness	6ft	TSTM3-134-6
		8ft	TSTM3-134-8
		12ft	TSTM3-134-12
		24ft	TSTM3-134-24
		Custom	TSTM3-134-NSS

TopMountTrack Product Codes

Carriage Packs

Item	Description	Code
	M6 (200lb) with no track stops	DKM0601
	M6 (200lb) with 1 track stop	DKM0611
	M6 (200lb) with 2 track stops	DKM0621
	M8 (500lb) with no track stops	DKM0801
	M8 (500lb) with 1 track stop	DKM0811
	M8 (500lb) with 2 track stops	DKM0821

© All copyright and other property in this document is reserved by Cavity Sliders USA Inc. Details and specifications are subject to change without notice. Whilst all care is taken to ensure the accuracy of all information, no responsibility will be accepted for any errors or omissions. 12/2024

CavitySliders.com

sales@cavitysliders.com

(888) 466-0030



Specs and Instructions

